VISTA WHITE

GRADING: MULTI STRIP
STAINING: WHITE
Art no 310201





Vista White is a light-toned hardened wood floor with a matt lacquered finish. The Multi-strip grading provides some natural colour variations and visible knots, creating a lively flooring experience.

PRODUCT DETAILS

PRODUCT Woodura Planks 3.0
WOOD TYPE Oak
DIMENSIONS 2030 × 200 × 9 mm
TYPE OF FLOORING Hardened wood
GRADING Multistrip
BEVEL Long- and short side
CORE Välinge Compositek core
THICKNESS WEAR LAYER 0.6 mm
SURFACE TREATMENT UV cured acrylic

PACKAGING

PLANKS PER PACKAGE 6
AREA PER PACKAGE 2.436 m²
NET WEIGHT 8.990 kg/m²
WEIGHT OF PACKAGE 21.9 kg

CLASSIFICATION	Standard	Result
FIRE RESISTANCE	EN 13501	Cfl-S1
THERMAL CONDUCITIVITY	EN 12664	0.12 W/(m x K)
THERMAL RESISTANCE	EN 12667	0.075 (m² x K)/W
FORMALDEHYDE EMISSION	EN 717-1	E1
BRINELL HARDNESS	EN 1534	8 HB (mv)
IMPACT RESISTANCE	EN 14354	EC2
THICKNESS SWELLING	EN 14354	<10%
WEAR RESISTANCE	EN 14354	>2000 cycles*
SLIP RESISTANCE	EN 14342:2013	EU: With slider 55: 66 GB: With slider 96: 62
STEP SOUND REDUCTION WHEN USING 2 MM UNDERLAY FOAM	EN ISO 10140-3 EN ISO 717-2	18-20 dB

* When tested on a flat surface

EASY INSTALLATION

The leakproof 5G Dry® floor locking system is well-known for providing the easiest, fastest and most reliable installation. No tools, glue or nails are needed – just click the pieces together. This floor is invented for a floating installation on top of the subfloor.

5G DRY

woodura™

FSC www.fsc.org

The mark of responsible forestry
FSC® C140725

NORDIC SWAN ECOLABEL
3029 0021

VISTA NATURAL

GRADING: MULTI STRIP
STAINING: NATURAL
Art no 310200





Vista Natural is a timeless hardened wood floor with a matt lacquered finish. The Multi-strip grading provides some natural colour variations and visible knots, creating a lively flooring experience.

PRODUCT DETAILS

PRODUCT Woodura Planks 3.0
WOOD TYPE Oak
DIMENSIONS 2030 × 200 × 9 mm
TYPE OF FLOORING Hardened wood
GRADING Multistrip
BEVEL Long- and short side
CORE Välinge Compositek core
THICKNESS WEAR LAYER 0.6 mm
SURFACE TREATMENT UV cured acrylic

PACKAGING

PLANKS PER PACKAGE 6
AREA PER PACKAGE 2.436 m²
NET WEIGHT 8.990 kg/m²
WEIGHT OF PACKAGE 21.9 kg

CLASSIFICATION	Standard	Result
FIRE RESISTANCE	EN 13501	Cfl-S1
THERMAL CONDUCITIVITY	EN 12664	0.12 W/(m x K)
THERMAL RESISTANCE	EN 12667	0.075 (m² x K)/W
FORMALDEHYDE EMISSION	EN 717-1	E1
BRINELL HARDNESS	EN 1534	8 HB (mv)
IMPACT RESISTANCE	EN 14354	EC2
THICKNESS SWELLING	EN 14354	<10%
WEAR RESISTANCE	EN 14354	>2000 cycles*
SLIP RESISTANCE	EN 14342:2013	EU: With slider 55: 66 GB: With slider 96: 62
STEP SOUND REDUCTION WHEN USING 2 MM UNDERLAY FOAM	EN ISO 10140-3 EN ISO 717-2	18-20 dB

* When tested on a flat surface

EASY INSTALLATION

The leakproof 5G Dry® floor locking system is well-known for providing the easiest, fastest and most reliable installation. No tools, glue or nails are needed – just click the pieces together. This floor is invented for a floating installation on top of the subfloor.

5G DRY

woodura™

FSC www.fsc.org

The mark of responsible forestry
FSC® C140725

NORDIC SWAN ECOLABEL
3029 0021

VISTA BROWN

GRADING: MULTI STRIP
STAINING: BROWN
Art no 310202

Vista Brown is a rich-toned hardened wood floor with a matt lacquered finish. The Multi-strip grading provides some natural colour variations and visible knots, creating a lively flooring experience.





PRODUCT DETAILS

PRODUCT Woodura Planks 3.0
WOOD TYPE Oak
DIMENSIONS 2030 × 200 × 9 mm
TYPE OF FLOORING Hardened wood
GRADING Multistrip
BEVEL Long- and short side
CORE Välinge Compositek core
THICKNESS WEAR LAYER 0.6 mm
SURFACE TREATMENT UV cured acrylic

PACKAGING

PLANKS PER PACKAGE 6
AREA PER PACKAGE 2.436 m²
NET WEIGHT 8.990 kg/m²
WEIGHT OF PACKAGE 21.9 kg

CLASSIFICATION	Standard	Result
FIRE RESISTANCE	EN 13501	Cfl-S1
THERMAL CONDUCITIVITY	EN 12664	0.12 W/(m x K)
THERMAL RESISTANCE	EN 12667	0.075 (m² x K)/W
FORMALDEHYDE EMISSION	EN 717-1	E1
BRINELL HARDNESS	EN 1534	8 HB (mv)
IMPACT RESISTANCE	EN 14354	EC2
THICKNESS SWELLING	EN 14354	<10%
WEAR RESISTANCE	EN 14354	>2000 cycles*
SLIP RESISTANCE	EN 14342:2013	EU: With slider 55: 66 GB: With slider 96: 62
STEP SOUND REDUCTION WHEN USING 2 MM UNDERLAY FOAM	EN ISO 10140-3 EN ISO 717-2	18-20 dB

* When tested on a flat surface

EASY INSTALLATION

The leakproof 5G Dry® floor locking system is well-known for providing the easiest, fastest and most reliable installation. No tools, glue or nails are needed – just click the pieces together. This floor is invented for a floating installation on top of the subfloor.

5G DRY

woodura™

FSC www.fsc.org

The mark of responsible forestry
FSC® C140725

NORDIC SWAN ECOLABEL
3029 0021